



# dBx Professional Soundproofing Board

High Performance Soundproofing Board for  
Walls, Ceilings and Floors

## TECHNICAL SPECIFICATIONS

Length x Width: 1200mm x 800mm (0.96m<sup>2</sup>)

Thickness: 8.5mm, 10mm, 15mm

Weight/m <sup>2</sup> :	8.5mm	13.2 kg
	10mm	14.8 kg
	15mm	22.0 kg

Impact Performance: Ln,w(c1) dB	8.5mm	up to 52dB
	10mm	up to 53dB
	15mm	up to 49dB

Airborne Performance: Rw (C:Ctr) dB	8.5mm	up to 67dB
	10mm	up to 68dB
	15mm	up to 70dB

Flammable Material Class: B1 (B-s1.d0)

Scope of Application: Interior

Applications: Separating Walls, Floors and ceilings in Domestic Properties  
Party Walls  
Commercial Walls, Floors and Ceilings  
Music Rooms, Performance Spaces and Studios

- Made in Great Britain, using only British sourced Materials.
- Manufactured in Dorset from Fully sustainable and recyclable materials.
- Engineering Grade Corrugated sheet board filled with fine Kiln dried Sand
- Excellent Airborne and Impact Reductions



LSP Supply Limited guarantee the quality of our products and reserve the right to technical changes with further development of our products. The data and information in this document is based on scientific and practical installation experience and corresponsive with data provided. We have no influence on the installation of these products on site and cannot guarantee the performance due to external factors.