



# Knauf Joint Filler Premium

Knauf Joint Filler Premium is a fast-setting gypsum compound for bedding tapes and beads by hand application. Up to a Q2 finish.

*Product-Data-Sheet*



## Areas of Application

For jointing of gypsum boards. For bedding joint tapes.

## Compliance Standards

EN13963. Type 3B

## Key Benefits

- Fast setting (120 minutes)
- Approximately 90 minute working time
- Smooth finish, easy to sand

**Build on us.**

Creation Date: 02/11/2023  
Revision Reference: 002  
Revision Date: 04/03/2025

## Performance Data

Reaction to Fire (R2F)	Flexural Strength (F)	Dangerous Substances (DS)
A1	NPD	NPD

## Technical Information

Colour	Weight (kg)	Approximate Coverage (m <sup>2</sup> )*	Material Number
White/grey	10	55m <sup>2</sup> per 10kg bag*	622340
White/grey	20	110m <sup>2</sup> per 20kg bag*	622342

\*Based on filling application to tapered edge board

## Sustainability

### Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

## Storage and Handling

Store in a dry area, protected from frost, high temperature and exposure to direct sunlight.

## Packaging

Paper sack with an inner plastic layer for protection.

## Shelf Life/Service Life

9 months from the date of production, which is printed on the bag.

## Disposal/Repair

Dispose of contents/container in accordance with licensed collectors sorting instructions.

## Health & Safety

Impermeable protective gloves, safety glasses with side shields due to splashing, and a dust mask when sanding are recommended. For full information, please refer to the safety data sheet.

## Application / Installation

Add the powder to 6.8L per 10kg bag of cold, clean water in a suitable clean mixing container. Mix to workable consistency. Mixed product is workable for approximately 90 minutes. Drying time approximately 120 minutes depending on conditions. Once the jointing is completed and dry, a coat of Knauf Wallboard Primer should be applied before decoration.

## Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

### Product Accreditations:



### Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given.  
Updates will not be automatically issued © Copyright Knauf 2024

### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

Tel: 0800 521050 (option 2)  
Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 02/11/2023  
Revision Reference: 002  
Revision Date: 04/03/2025